

Republic of the Philippines
Department of the Interior and Local Government
NATIONAL POLICE COMMISSION
Makati City

Resolution No. 2005-015

**PRESCRIBING THE STANDARD SPECIFICATIONS FOR
PRISONER'S VAN**

WHEREAS, Section 14 paragraph (a), sub-paragraphs (5) and (8), of Republic Act 6975 as amended by Section 5 of Republic Act 8551 empowers the Commission to "approve or modify plans and programs on education and training, logistical requirements, communications, records, information system, crime laboratory, crime prevention and crime reporting "as well as" prescribe minimum standards for arms, equipment and uniforms and, after consultation with the Philippine Heraldry Commission, for insignia of ranks, awards and medals of honor";

WHEREAS, in pursuance with the aforecited legal prescription, the PNP, through its Uniform and Equipment Standardization Board (UESB), has favorably submitted and indorsed UESB Resolution No. 2004-06, dated June 04, 2004, proposing the standard specifications for Prisoner's Van for consideration of the Commission;

WHEREAS, the PNP is in need of additional vehicles such as a Prisoner's Van to enhance its operational mobility and maintain tighter security in transporting prisoners to and from the different detention centers and in attending court hearings;

WHEREAS, upon careful evaluation of the proposed specifications, modifications were introduced so that the engine displacement's requirement will have a variable range of 2200cc to 2800cc only and the wheelbase be set at 2200mm (minimum) so as not to favor nor benefit a particular supplier or manufacturer.

NOW THEREFORE, the Commission in the exercise of its statutory power to administer and control the PNP, **HAS RESOLVED TO ADOPT AND PRESCRIBE AS IT HEREBY ADOPTS AND PRESCRIBES** the following standard specifications for the Prisoner's Van for the guidance of the PNP in the procurement and use of the same to read as follows;

I. SPECIFICATIONS

1. Engine:
 - 1.1 Fuel : Diesel
 - 1.2 Piston : 2200cc – 2800cc
 - Displacement : 70 or higher
 - 1.3 Horsepower : 14 kg-m or higher
 - 1.4 Torque
2. Vehicle Type: Bonnet-type or cab-over-engine type
 3. Transmission : Manual, 4-speed or better.
 4. Drive Configuration: 4 x 2
 5. Suspension
 - 5.1 Front : Leaf or coil spring
 - 5.2 Rear : Leaf spring
 6. Wheel /Rim: 14-16 inch, pressed steel rim.
 7. Steering: Left-hand drive, power assisted.
 8. Aircon System: Dual Aircon
 9. Brakes System
 - 9.1 Hydro Vac dual circuit
 - 9.2 Provided with parking /hand brake.
 10. Body and Frame : Separate cab and body.
 - 10.1 Wheelbase : 2200mm (minimum)
 - 10.2 Overall : 4200mm (minimum)Length
 - 10.3 Overall : 2500mm (maximum)Height
 - 10.4 Provided with sliding side windows, rear swing door with glass windows
 - 10.5 The rear signal lights shall be protected by a 10mm diameter stainless steel rod.
 11. Outside Grills /Screen:
 - 11.1 The side windows shall be protected by grills made of ¼ - inch diameter steel spaced at 2 inches apart.
 - 11.2 The tip of the grill shall be fully welded to a 4.5 x 19mm flat bar frame and shall be sandwiched by another 4.5 x 19mm flat bar.
 - 11.3 The 4.5 x 25mm flat bar frame shall be bolted or riveted to the side of the vehicle.
 - 11.4 The grill should not touch the side windows.
 - 11.5 The intersection of the grills shall be welded.
 - 11.6 The windshield and the cab side windows shall be protected by a 1/8 – inch diameter screen wire spaced at 2 inches apart.

12. Prisoner's Area /Cubicle:
 - 12.1 The frames of the partition and the door shall be 2 inches diameter steel pipe.
 - 12.2 The frames of the partition and the door shall follow the contour of the ceiling, walls, seats and flooring and shall be rigidly attached to it.
 - 12.3 The partition grills shall be ¼ - inch diameter steel
 - 12.4 The tip of the grills shall be welded to the steel pipe and shall be sandwiched by a 4.5 x 19mm flat bar which is also fully welded to the steel pipe.
 - 12.5 The partition door shall be 500mm width and maximum height.
 - 12.6 The partition door shall be secured by a 20mm diameter barrel bolt with heavy duty padlock and another heavy duty padlock.
 - 12.7 The tube to which the barrel bolt slides shall be fully welded to a 4.5mm thick B. I. sheet.
 - 12.8 The front window of the body of the vehicle shall be secured by ¼ - inch diameter steel welded to a 4.5 x 19mm flat bar. The construction of which shall be the same as that of the outside grills.
 - 12.9 The partition shall be constructed 800mm from the end of the body of the vehicle.
 - 12.10 The grill shall be painted white.

13. Color and Markings: White with appropriate markings specified in NAPOLCOM Res. No. 99-002 dated January 5, 1999 (Approving the Standard Color and Markings for PNP Motor Vehicles, Seacraft and Aircraft).

14. Vehicle Equipment /Accessories
 - 14.1 1 each siren, 4-programs with PA system
100W amplifier and 150W speaker or better
 - 14.2 1 each blinker /rotary light, horizontal type, aerodynamic design mounted on the cab, color: blue and red.
 - 14.3 OVM Tools
 - 14.4 Hydraulic Jack
 - 14.5 Spare tire with rim
 - 14.6 Tire wrench
 - 14.7 AM /FM radio with cassette player

15. Requirements:
 - 15.1 Maintenance Manual
 - 15.2 Operation Manual

II. WARRANTY


Three (3) years or 100,000 kms whichever comes first, and five (5) years on spare parts /service centers.

(p)

III. Must pass the PNP functional Test.

Note: Items /data not mentioned in the specification shall form part of the standard offer as indicated in the brochure /technical specifications.

ADOPTED this 11th day of JANUARY 2005, at Makati City.



[Signature]
ANGELO T. REYES
Chairman

[Signature]
IMELDA CRISOL-ROCES
Vice-Chairman & Executive officer

[Signature]
LINDA L. MALENAB-HORNILLA
Commissioner

[Signature]
CELIA SANIDAD-LEONES
Commissioner

MIGUEL G. CORONEL
Commissioner *for LEAVE*

[Signature]
EDGAR B. AGLIPAY
Ex-officio Commissioner

Attested By:

[Signature]
ADELMALYN A. MUNIEZA
Chief, Secretariat